

Cassette

Chilled Water Fan Coil Unit 12,000-48,000 BTH/H Cassette Models CWS Series 50 Hz Trane is proud to present the latest elegant design of Cassette chilled water fan coil. This chilled water fan coil unit is carefully manufactured according to Trane Worldwide Quality Standard to provide you years of comfort and convenient cooling with minimal service requirement.

Elegant Design

- 4-way airflow that can distribute cool air throughout the room.
- Do not disturb your relaxation due to is very low noise operation.
- With its height only 310 mm shall fit well with limited ceiling space.

DC motor Advantage

With the latest technology of DC motor used in CWS series, it will provide you continuous comfort with very low operation noise. Besides, DC motor will help save significant energy consumption of the fan coil unit compared with the normal AC motor type.

Digital Wireless Remote Control

- 4-fan speed control Turbo, Hi, Me, Lo and Auto.
- Programmable timer user can set time to automatically turn on or off unit in advance.
- Auto swing function automatically help distribute airflow efficiently throughout the room.





Product Specifications

Models	CFM	EWT (Deg F)	Cooling Capacity (MBH)		GPM	Pressure Drop (Ft of Water)	Dimensions HxWxD (mm)		Water Inlet & Outlet Con-
			Total	Sensible		(i t oi water)	Housing	Front Panel	nection (in)
		40	17.06	11.20	3.40	7.50			
CWS047A	400	45	12.04	9.17	2.40	4.02	280 x 572 x 572	70 x 720 x 720	3/4
		50	6.84	6.72	1.36	1.49			
	600	40	26.1	17.08	5.20	12.12	280 x 572 x 572	70 x 720 x 720	3/4
CWS067A		45	19.52	15.12	3.89	7.19			
		50	13.19	12.80	2.63	3.58			
CWS087A	800	40	34.41	22.54	6.85	13.77	310 x 842 x 842	70 x 950 x 950	1
		45	24.49	18.52	4.88	7.50			
		50	13.05	12.83	2.60	2.48			
CW\$107A	1,000	40	42.11	27.63	8.39	13.61	310 x 842 x 842	70 x 950 x 950	1
		45	30.88	24.56	6.16	7.80			
		50	19.81	18.98	3.95	3.55			
		40	52.51	34.46	10.46	14.82			
CWS127A	1,200	45	37.19	28.27	7.41	8.00	310 x 842 x 842	70 x 950 x 950	1
		50	19.33	18.41	3.86	2.54	1	1	
		40	58.64	38.66	11.68	16.59			
CWS147A	1,400	45	42.19	32.02	8.41	9.20	310 x 842 x 842	70 x 950 x 950	1
		50	24.36	23.94	4.86	3.49			
		40	65.71	37.99	13.09	19.34			
CWS167A	1,600	45	48.01	31.73	9.57	11.00	310 x 842 x 842	70 x 950 x 950	1
		50	30.64	26.14	6.11	4.97			

Note: Capacity rating is based on 10 deg F water temperture rise and entering air temperature is 80 FDB / 67 FWB













Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$13 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.tranethailand.com

TRANEThailand

Airco Limited 30th - 31st Floor, Vanit Building II 1126/2 New Petchburi Road, Makkasan, Rachthevee, Bangkok 10400



